

Specifications

Lyric Features

CD reading Cyrus SE₂ custom disc management

D/A converter..... 32 bit

Connectivity

Network Wired ethernet RJ45 or Wi-fi 802.11g

Bluetooth version A2DP

Digital inputs..... 2 x Toslink optical

..... 2 x RCA coaxial

Analogue input 1 x RCA stereo

USB A 2 x ports for iPad, USB flash drive or HDD

USB B 1 x port for a computer

Network streaming

Compatible file formats

... WAV, AIFF, FLAC (up to 24 bit/192 k)

..... MP3 (up to 320kB/s VBR/CBR)

..... Ogg Vorbis, WMA, ALAC, AAC

Internet radio

Service provider TuneIn radio, full service

Radio tuner

Coverage FM Band II, DAB Band III and L-Band

Lyric Performance

Power supply See rating marked on the unit

Power consumption 430 W

Dimensions 420 (W) x 105 (H) x 320 (D) mm

Weight..... 8.88 kg

Outputs

Output power//8 Ω..... 150 W

Output power//6 Ω..... 230 W

Pre out (max) 2.5 V

Digital inputs

THD+n (1 kHz, 50 W)..... 0.008 %

S/n ratio (ref 1W) -70 dB

Digital input voltage..... 500 mV pk-pk

Digital input Impedance..... 75 Ω

Digital audio formats PCM stereo only

Sample rate range..... 32 k - 192 k

Analogue input

THD+n (1kHz, 50 W)..... 0.012 %

S/n ratio (ref 1W) -70 dB

Input sensitivity (for 170W output) 530 mV

Tuner

DAB tuning range (Band III)..... 174.928 - 239.200 MHz
(L-Band) .. 1452.960 - 1490.624 MHz

DAB sensitivity -100 dBm (typ)

DAB frequency response..... 20 Hz - 20 kHz

DAB THD+n 0.01 (typ)

DAB s/n ratio..... >95 dB

FM tuning range:..... 87.5 - 108 MHz

FM sensitivty..... -107 dBm (typ)

FM THD+n 0.15 % (typ)

FM S/n ratio:..... >64.5 dB

FM stereo separation:..... >30 dB

USB drive

Compatible formats FAT16, FAT32

Cyrus reserves the right to change all specifications without notice. E & OE