

- Class leading 3D Blu-Ray player
- 4k upscaling from all video sources
- Blu-Ray, DVD, SACD & CD playback
- UPnP and CIFS audio and video streaming
- Audiophile grade music playback
- TI/Burr Brown PCM1794 DAC
- Balanced and single-ended audio outputs
- IR and full duplex IP & RS232 control
- Low power 0.5W standby

Few specialist manufacturers have ever stepped up to the plate where development of video playback is concerned. The technological know-how required for the successful design of high performance video sources is vast. With more than ten years of digital video experience, not to mention global recognition of its efforts, Arcam is proud to announce the arrival of its newest disc player, the UDP411.

The UDP411 embraces movie and music playback, offering outstanding performance in both disciplines. Unlike most Blu-Ray machines music from SACD & CD is delivered with outstanding quality while movie performance with either 2D or 3D films is to the very highest standards currently available. Using Arcam's unique and hard won engineering expertise the UDP411 delivers a truly emotional portrayal of your favourite discs, delivering blockbuster experiences straight to your arm chair.

The UDP411 uses a very simple, almost direct video path from the disc or network video with upscaling of all video sources up to 4k to its ultra-high precision outputs. This short path approach allows pictures to be presented without unintentional artefacts and delivers the kind of pristine picture quality that will truly captivate any viewer. Using broadcast quality digital video clocks during processing means the resulting picture quality is simply stunning.

To ensure the UDP411's music performance meets the same "reference" standards the class leading TI/Burr Brown PCM1794 digital to analogue converter (DAC) is used. This device, coupled with a linear phase Bessel output filter and high precision re-clocking system results in audio quality comparable to a dedicated audiophile CD player. Even the UDP411's power supply has been specially designed for outright performance. Discreet sub-regulated power supplies on the drive, audio and DAC boards deliver significant benefits to the overall performance of each element and thus allow each section to work truly independently and without interference.

"Amazing video and access to content on my network, I LOVE it!"

Matt Frost - Support Engineer, Arcam



UPnP and CIFS compatibility allow for effortless integration into networks allowing the UDP411 to access stored content with ease.

As with all its FMJ devices, Arcam has gone to incredible lengths to maximise the performance of this next generation player. As an example the UDP411 benefits from a critically damped cover and chassis to virtually eliminate damaging microphonic vibration from reaching the sensitive electronics inside.

The UDP411 is designed with a single purpose; to deliver the very best music and movie experience for discerning owners. It also features a full suite of discrete IR, IP and RS232 codes making it perfect for integration within a high performance home cinema installation.

The UDP411 is designed in the UK and is available in a discrete black finish.

Available
Q3
2014

Arcam, The West Wing, Stirling House, Waterbeach, Cambridge CB25 9PB, UK. www.arcam.co.uk

Preliminary information only. Arcam has a policy of continuous improvement; we reserve the right to change features without notice. E&OE 2014

Arcam is a trademark of A&R Cambridge Ltd. All other trademarks are the property of their respective owners



Analogue Audio Output	
Digital to Analogue conversion	24-bit 192kHz Delta-Sigma DAC
Signal to noise ratio	110dB CCIR
Harmonic distortion (1kHz)	0.002%
Frequency response (± 0.5 dB)	10Hz–20kHz
Output level (0dB)	2.2Vrms
Output impedance	47 Ω
Minimum recommended load	5k Ω
Video Outputs	
HDMI	19-pin HDMI connector Supported video formats are: 720 x 576p, 720(1440) x 576i, 720 x 480p, 720(1440) x 480i, 1280 x 720p, 1920 x 1080i, 1920 x 1080p, 3840 x 2160p Audio to 8-channel/96kHz or 2-channel/192kHz (24-bit).
Digital interfaces	
USB	USB 2.0 High Speed (480 Mbit/s)
Network	10 BASE-T / 100 BASE-TX
Physical	
Dimensions	W433 x D400 x H100mm
Weight	6.2kg nett/8.5kg packed
Power consumption	20W maximum
Digital output connection	75 Ω co-axial optical TOSLINK
Supplied accessories	
	Mains lead CR301 remote control 2 x AAA batteries Wi-Fi antenna
E&OE	
NOTE: All specification values are typical unless otherwise stated	

* "Dolby TrueHD", "Dolby Digital+", "Dolby Digital EX", "Dolby Pro Logic IIX" & "Dolby Volume" are trademarks of Dolby Laboratories Licensing Corporation. ** "DTS High Resolution Audio", "DTS-ES Discrete", "DTS-ES Matrix", "DTS96/24", "DTS Neo:6" are trademarks of Digital Theatre Systems.