




photo by Atlantic AV Networks, GB www.atlantikav.co.uk

www.dreamvision.net







P/N PASSIVE 3D PACK R9201704 R9201705 R9201706  SIGNAL COMPATIBILITY HDR content auto-detect, 4k streamling services and UHD Blu-ray disks up to 4K60p PARIE TECHNOLOGY  3-chip LCOS HD 0.7 inch panel OPTIC Full-glass Motorized Lens (zoom & focus) 1.4 -2.8:1 (2x zoom) OPTIC SLOTE COVER NO POSSITE COVER NO POSSITE (16:9)  60° - 240° diagonal LAMP CONSUMPTION 265 W NSH Bulb - up to 4 500 hours (with lamp used in low mode) Biniormiess (ANSI Lumens) 1 800 1 900 2 000 NATIVE Contrast Ratio 400 000:1 1 300 000:1 1 100 000:1  DYNAMIC CONTRAST RATIO 400 000:1 1 300 000:1 1 1 300 000:1 1 1 600 000:1  CMS FUNCTIONS  COLOR Modes REC.709 (HDTV) REC.709, DCI-P3 and BT.2020 EPERET CALIBRATION NO YES  PICTURE MODES 4 Presets + 5 Users Modes 4 Presets + THIX + 5 User Modes + 4 for Installation Expert only COLOR SPACE PROPILES NOSE LEVEL  Less than 20 dB (in low mode)  LIVEURS  AND PRESENSE + 5 Users NOSE LEVEL  LESS than 20 dB (in low mode)  LIVEURS  AND PRESENSE + 5 Users NOSE LEVEL  LESS than 20 dB (in low mode)  LIVEURS  AND PRESENSE + 5 Users NOSE LEVEL  LESS than 20 dB (in low mode)  LIVEURS  AND PRESENSE + 5 Users NOSE LEVEL  LESS than 20 dB (in low mode)  LIVEURS  AND PRESENSE + 5 Users NOSE LEVEL  LESS than 20 dB (in low mode)  LIVEURS  AND PRESENSE + 5 Users NOSE LEVEL  LESS than 20 dB (in low mode)  LIVEURS  AND PRESENSE + 5 Users NOSE LEVEL  AND PRESENSE	Model Name	SIGLOS Ultra 1	SIGLOS Ultra 2	SIGLOS Ultra 3
DISPLAY RESOLUTION   3840 x 2160 (4K Resolution)	P/N STANDARD PACK	R9201701	R9201702	R9201703
STORM. COMPATIBILITY	P/N Passive 3D Pack	R9201704	R9201705	R9201706
PANEL TECHNOLOGY   3-chip LCOS HD 0.7 inch panel	DISPLAY RESOLUTION	3840 x 2160 (4K Resolution)		
OPTIC         Full-glass Motorized Lens (zoom & focus) 1.4 - 2.8:1 (2x zoom)           OPTIC SLIDE COVER         No         Yes           SCREN OFFSET         Motorized Optical Shift +/- 80% vertically +/- 34% horizontally           SCREN SIZE (16:9)         60° - 240° diagonal           LAMP CONSUMPTION         265 W NSH Bulb - up to 4500 hours (with lamp used in low mode)           BRIGHTNESS (ANSI LUMENS)         1800         1900         2 000           NATIVE CONTRAST RATIO         40 000:1         130 000:1         160 000:1           COLOR MODES         REC.709 (HDTV)         REC.709, DCI-P3 and BT.2020           EPPERT CALIBRATION         NO         YES           PICTURE MODES         4 Presets + 5 User Modes         4 Presets + 7HX + 5 User Modes + 4 for Installation Expert only           COLOR SPACE PROPILES         9 Presets + 5 Users         12 Presets + 5 Users           Noise Level.         Less than 20 dB (in low mode)           HOME-CINEIA         Low Latency mode for real time simulation and ultimate gaming experiences           PROCESSING         PERCENTINE         2x HDMI 2.00 inputs (with HDR support)           HOME-CINEIA         HDR PICTURE modes with Perceptual Quantization (PQ) EOTF and Hybrid Log gamma           HOWE-CINEIA         HOWE-CINEIA         100 pixel adjustment in 81 individual zones           WEIGHT	SIGNAL COMPATIBILITY	HDR content auto-detect,4K streaming services and UHD Blu-ray disks up to 4K60p		
OPTIC SLIDE COVER         No         Yes           SCREEN OFFSET         Motorized Optical Shift +/- 80% vertically +/- 34% horizontally           SCREEN SIZE (16:9)         60" - 240" diagonal           LAMP CONSUMPTION         265 W NSH Bulb - up to 4500 hours (with lamp used in low mode)           BETGITINESS (ANSI LUMENS)         1 800         1 900         2 000           NATIVE CONTRAST RATIO         40 000:1         1 30 000:1         1 600 000:1           CMS FUNCTIONS         YES (6-Axis)           COLOR MODES         REC.709 (HDTV)         REC.709, DCI-P3 and BT.2020           EPPERT CALIBRATION         NO         YES           PICTURE MODES         4 Presets + 5 User Modes         4 Presets + 5 User Modes + 4 for Installation Expert only           COLOR SPACE PROPILES         9 Presets + 5 Users         12 Presets + 5 Users           NOISE LEVEL         Less than 20 dB (in low mode)           HORE-CINEMA VIDEO PROCESSING         HDR PICture modes with Perceptual Quantization (PQ) EOTE and Hybrid Log gamma Low Latency mode for real time simulation and ultimate gaming experiences           BULR REQUISION AND PROCESSING         Frame Packing, Side-by-Side, Top & Bottom - 3D anamorphic V-Stretch           PIXEL ALIGNMENT         1/16 pixel adjustment in 81 individual zones           WEIGHT         14.3 kg (31.5 lbs)         15.1 kg (33.3 lbs)	PANEL TECHNOLOGY	3-chip LCOS HD 0.7 inch panel		
	Ортіс	Full-glass Motorized Lens (zoom & focus) 1.4 -2.8:1 (2x zoom)		
Color Space Profiles   Series + 5 Users   Less than 20 dB (in low mode)	OPTIC SLIDE COVER	No Yes		
LAMP CONSUMPTION  265 W NSH Bulb - up to 4500 hours (with lamp used in low mode)  BRIGHTHESS (ANSI LUMENS)  1800  1900  2000  NATIVE CONTRAST RATIO  400 000:1  130 000:1  1600 000:1  1600 000:1  CMS FUNCTIONS  REC.709 (HDTV)  REC.709, DCI-P3 and BT.2020  EXPERT CALIBRATION  NO  YES  PICTURE MODES  4 Presets + 5 User Modes  4 Presets + THX + 5 User Modes + 4 for Installation Expert only  COLOR SPACE PROFILES  9 Presets + 5 Users  12 Presets + 5 Users  NOISE LEVEL  Less than 20 dB (in low mode)  HDR Picture modes with Perceptual Quantization (PQ) EOTF and Hybrid Log gamma  Low Latency mode for real time simulation and ultimate gaming experiences  Blur Reduction and enhanced 400Hz Crystal Motionia  HOMP-CINEMA  Video Processing  Type (with HDCP 2-2 and 18 Gbps transmission band)  HDR Picture modes with Perceptual Quantization (PQ) EOTF and Hybrid Log gamma  Low Latency mode for real time simulation and ultimate gaming experiences  Blur Reduction and enhanced 400Hz Crystal Motionia  Rew True Cinema Black V (with HDR support)  4K Interpolation (3840 x 2160)  3D COMPATIBILITY  Frame Packing, Side-by-Side, Top & Bottom - 3D anamorphic V-Stretch  PIXEL ALIGNMENT  14.3 kg (31.5 lbs)  15.1 kg (33.3 lbs)  DIMENSIONS (LXWAH)  505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)  HOME AUTOMATION  RS-232 (Dsub 9) / LAN R345 / 12V Trigger  YES V+/- 16° (not in 3D Mode)  POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  Box DIMENSIONS  61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  Options	SCREEN OFFSET	Motorized Optical Shift +/- 80% vertically +/- 34% horizontally		
Native Contrast Ratio	SCREEN SIZE (16:9)	60" - 240" diagonal		
NATIVE CONTRAST RATIO	LAMP CONSUMPTION	265 W NSH Bulb - up to 4 500 hours (with lamp used in low mode)		
DYNAMIC CONTRAST RATIO	BRIGHTNESS (ANSI LUMENS)	1 800	1 900	2 000
CMS FUNCTIONS  COLOR MODES  REC.709 (HDTV)  REC.709, DCI-P3 and BT.2020  EXPERT CALIBRATION  NO  YES  PICTURE MODES  4 Presets + 5 User Modes  4 Presets + 5 User Modes + 4 for Installation Expert only  COLOR SPACE PROFILES  9 Presets + 5 Users  12 Presets + 5 Users  NOISE LEVEL  Less than 20 dB (in low mode)  INPUTS  2x HDMI 2.0b inputs (with HDCP 2.2 and 18 Gbps transmission band)  HDR Picture modes with Perceptual Quantization (PQ) EOTF and Hybrid Log gamma Low Latency mode for real time simulation and ultimate gaming experiences Blur Reduction and enhanced 4001z Crystal Motion® new True Chemia Black V (with HDR support) 4K Interpolation (3840 x 2160)  3D COMPATIBILITY  Frame Packing, Side-by-Side, Top & Bottom - 3D anamorphic V-Stretch  Pixel Alignment  1/16 pixel adjustment in 81 individual zones  Weight  14.3 kg (31.5 lbs)  15.1 kg (33.3 lbs)  DIMENSIONS (LXWXH)  505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)  HOME AUTOMATION  RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger  DIGITAL KEYSTONE  YES V+/- 16° (not in 3D Mode)  POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by Box DIMENSIONS  61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  Options  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	NATIVE CONTRAST RATIO	40 000:1	130 000:1	160 000:1
REC.709 (HDTV) REC.709, DCI-P3 and BT.2020  EXPERT CALIBRATION NO YES  PICTURE MODES 4 Presets + 5 User Modes 4 Presets + 5 User Modes 4 Presets + 5 User Modes + 4 for Installation Expert only COLOR SPACE PROFILES 9 Presets + 5 Users 12 Presets + 5 Users NOISE LEVEL Less than 20 dB (in low mode)  INPUTS 2x HDMI 2.0b inputs [with HDCP 2.2 and 18 Gbps transmission band] HDR Picture modes with Perceptual Quantization (PQ) EOTF and Hybrid Log gamma Low Latency mode for real time simulation and ultimate gaming experiences Blur Reduction and enhanced 400Hz Crystal Motion® new True Cinema Black V (with HDR support) 4K Interpolation (3840 x 2160)  3D COMPATIBILITY Frame Packing, Side-by-Side, Top & Bottom - 3D anamorphic V-Stretch  PIXEL ALIGNMENT 1/16 pixel adjustment in 81 individual zones  WEIGHT 14.3 kg (31.5 lbs) 15.1 kg (33.3 lbs)  DIMENSIONS (LxWxH)  S05 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)  HOME AUTOMATION RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger  DIGITAL KEYSTONE YES V+/- 16° (not in 3D Mode)  POWER AND CONSUMPTION AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by BOX DIMENSIONS 61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  OPTIONS 3D Glasses, anamorphic kit, Celling Mount kit, Motorized Lift, special colors and finishes, screens	DYNAMIC CONTRAST RATIO	400 000:1	1 300 000:1	1 600 000:1
PICTURE MODES  4 Presets + 5 User Modes + 4 for Installation Expert only  COLOR SPACE PROFILES  9 Presets + 5 Users  12 Presets + 5 Users  Noise Level  Less than 20 dB (in low mode)  INPUTS  2x HDMI 2.0b inputs [with HDCP 2.2 and 18 Gbps transmission band]  HDR Picture modes with Perceptual Quantization (PQ) EOTF and Hybrid Log gamma Low Latency mode for real time simulation and ultimate gaming experiences  Blur Reduction and enhanced 400Hz Crystal Motion® new True Cinema Black V (with HDR support)  4K Interpolation (3840 × 2160)  3D COMPATIBILITY  Frame Packing, Side-by-Side, Top & Bottom - 3D anamorphic V-Stretch  PIXEL ALIGNMENT  1/16 pixel adjustment in 81 individual zones  WEIGHT  14.3 kg (31.5 lbs)  15.1 kg (33.3 lbs)  DIMENSIONS (LXWXH)  505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)  HOME AUTOMATION  RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger  DIGITAL KEYSTONE  YES V+/- 16° (not in 3D Mode)  POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  OPTIONS  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	CMS Functions	YES (6-Axis)		
PICTURE MODES  4 Presets + 5 User Modes  4 Presets + THX + 5 User Modes + 4 for Installation Expert only  COLOR SPACE PROFILES  9 Presets + 5 Users  12 Presets + 5 Users  Noise Level.  Less than 20 dB (in low mode)  IMPUTS  2 x HDMI 2.0b inputs [with HDCP 2.2 and 18 Gbps transmission band]  HDR Picture modes with Perceptual Quantization (PQ) EOTF and Hybrid Log gamma Low Latency mode for real time simulation and ultimate gaming experiences Blur Reduction and enhanced 400Hz Crystal Motion® new True Cinema Black V (with HDR support) 4K Interpolation (3840 x 2160)  3D COMPATIBILITY  Frame Packing, Side-by-Side, Top & Bottom - 3D anamorphic V-Stretch  Pixel Alignment  1/16 pixel adjustment in 81 individual zones  WEIGHT  14.3 kg (31.5 lbs)  15.1 kg (33.3 lbs)  DIMENSIONS (LxWxH)  505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)  HOME AUTOMATION  RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger  DIGITAL KEYSTONE  YES V+/- 16° (not in 3D Mode)  POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  Box DIMENSIONS  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	Color Modes	REC.709 (HDTV)	REC.709, DCI-P3 and BT.2020	
COLOR SPACE PROFILES       9 Presets + 5 Users       12 Presets + 5 Users         Noise Level.       Less than 20 dB (in low mode)         Inputs       2x HDMI 2.0b inputs [with HDCP 2.2 and 18 Gbps transmission band]         HOME-CINEMA VIDEO PROCESSING       HDR Picture modes with Perceptual Quantization (PQ) EOTF and Hybrid Log gamma Low Latency mode for real time simulation and ultimate gaming experiences         Blur Reduction and enhanced 400Hz Crystal Motion® new True Cinema Black V (with HDR support) 4K Interpolation (3840 x 2160)         3D COMPATIBILITY       Frame Packing, Side-by-Side, Top & Bottom - 3D anamorphic V-Stretch         PIXEL ALIGNMENT       1/16 pixel adjustment in 81 individual zones         WEIGHT       14.3 kg (31.5 lbs)       15.1 kg (33.3 lbs)         DIMENSIONS (LxWxH)       505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)         HOME AUTOMATION       RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger         DIGITAL KEYSTONE       YES V+/- 16° (not in 3D Mode)         POWER AND CONSUMPTION       AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by         Box DIMENSIONS       61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)         OPTIONS       3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	EXPERT CALIBRATION	NO	YES	
Less than 20 dB (in low mode)   Inputs   2x HDMI 2.0b inputs [with HDCP 2.2 and 18 Gbps transmission band]	PICTURE MODES	4 Presets + 5 User Modes	4 Presets + THX + 5 User Modes + 4 for Installation Expert only	
INPUTS  2x HDMI 2.0b inputs [with HDCP 2.2 and 18 Gbps transmission band]  HDR Picture modes with Perceptual Quantization (PQ) EOTF and Hybrid Log gamma Low Latency mode for real time simulation and ultimate gaming experiences Blur Reduction and enhanced 400Hz Crystal Motion® new True Cinema Black V (with HDR support) 4K Interpolation (3840 x 2160)  3D Compatibility  Frame Packing, Side-by-Side, Top & Bottom - 3D anamorphic V-Stretch  Pixel Alignment  1/16 pixel adjustment in 81 individual zones  Weight  14.3 kg (31.5 lbs)  15.1 kg (33.3 lbs)  DIMENSIONS (LxWxH)  505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)  Home Automation  RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger  DIGITAL KEYSTONE  YES V+/- 16° (not in 3D Mode)  POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  Box DIMENSIONS  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	Color Space Profiles	9 Presets + 5 Users	12 Presets + 5 Users	
HOME PICTUREMA VIDEO PROCESSING  HOME PROCESSING  HOME PROCESSING  HOME AUTOMATION  POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  BOW Latency mode for real time simulation and ultimate gaming experiences allow a part of the process of the	Noise Level	Less than 20 dB (in low mode)		
HOME-CINEMA VIDEO PROCESSING  Low Latency mode for real time simulation and ultimate gaming experiences Blur Reduction and enhanced 400Hz Crystal Motion® new True Cinema Black V (with HDR support) 4K Interpolation (3840 x 2160)  3D COMPATIBILITY  Frame Packing, Side-by-Side, Top & Bottom - 3D anamorphic V-Stretch  PIXEL ALIGNMENT  1/16 pixel adjustment in 81 individual zones  WEIGHT  14.3 kg (31.5 lbs)  15.1 kg (33.3 lbs)  DIMENSIONS (LXWXH)  505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)  HOME AUTOMATION  RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger  DIGITAL KEYSTONE  YES V+/- 16° (not in 3D Mode)  POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  BOX DIMENSIONS  61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  OPTIONS  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	INPUTS			
PIXEL ALIGNMENT  1/16 pixel adjustment in 81 individual zones  WEIGHT  14.3 kg (31.5 lbs)  15.1 kg (33.3 lbs)  DIMENSIONS (LxWxH)  505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)  HOME AUTOMATION  RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger  DIGITAL KEYSTONE  YES V+/- 16° (not in 3D Mode)  POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  Box DIMENSIONS  61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  OPTIONS  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens		Low Latency mode for real time simulation and ultimate gaming experiences Blur Reduction and enhanced 400Hz Crystal Motion® new True Cinema Black V (with HDR support)		
WEIGHT  14.3 kg (31.5 lbs)  15.1 kg (33.3 lbs)  DIMENSIONS (LXWXH)  505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)  RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger  DIGITAL KEYSTONE  YES V+/- 16° (not in 3D Mode)  POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  Box DIMENSIONS  61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  OPTIONS  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	3D COMPATIBILITY	Frame Packing, Side-by-Side, Top & Bottom - 3D anamorphic V-Stretch		
DIMENSIONS (LxWxH)  505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)  RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger  DIGITAL KEYSTONE  YES V+/- 16° (not in 3D Mode)  POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  Box DIMENSIONS  61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  OPTIONS  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	PIXEL ALIGNMENT	1/16 pixel adjustment in 81 individual zones		
HOME AUTOMATION  RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger  PIGITAL KEYSTONE  YES V+/- 16° (not in 3D Mode)  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  Box dimensions  61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  Options  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	WEIGHT	14.3 kg (31.5 lbs)		
DIGITAL KEYSTONEYES V+/- 16° (not in 3D Mode)POWER AND CONSUMPTIONAC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-byBOX DIMENSIONS61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)OPTIONS3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	DIMENSIONS (LXWXH)	505 x 455 x 215 mm (19.9 x 17.9 x 8.5 inches)		
POWER AND CONSUMPTION  AC 110~240V 50/60Hz 360 W / 4.8 W in stand-by / 0.4W in Eco-Mode stand-by  Box dimensions  61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  Options  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	HOME AUTOMATION	RS-232 (Dsub 9) / LAN RJ45 / 12V Trigger		
Box DIMENSIONS  61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)  Options  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	DIGITAL KEYSTONE	YES V+/- 16° (not in 3D Mode)		
OPTIONS  3D Glasses, anamorphic kit, Ceiling Mount kit, Motorized Lift, special colors and finishes, screens	Power and Consumption			
	Box dimensions	61x58x41 cm 19.5 kg (67x66x52 cm - 21.5 kg when shipped individually)		
Passive 3D Kit B.E.S.T. 3D Passive Kit for Siglos Series	Options	3D Glasses, anamorphic kit, Co	eiling Mount kit, Motorized Lift, spec	ial colors and finishes, screens
	Passive 3D Kit	B.E.S.T. 3D Passive Kit for Siglos Series		

