

## Specifications

### Connectivity:

Stereo balanced analog audio outputs: 1 set

Stereo unbalanced analog audio outputs: 1 set

Digital audio outputs: 1 Coax S/PDIF; 1 Toslink optical S/PDIF; 1 AES/EBU electrical

### Formats Supported:

Stereo audio CDs; (Red Book standard); prerecorded or computer recorded

MP3 audio CDs; prerecorded or computer recorded CDs containing two channel MP3 audio files

The stereo audio CD layer (Red Book standard) from Hybrid SACDs

### Output Level:

Balanced outputs: +12 dBV (4 V RMS; 11 V P-P)

Unbalanced outputs: +6 dBV (2 V RMS; 5.5 V P-P)

### Frequency Response:

10 Hz - 20 kHz +/- 0.04 dB

### THD:

< 0.002% @ 1 kHz

< 0.015% (20 Hz - 20 kHz)

### IMD (SMPTE 4:1):

< 0.005%

### Crosstalk:

< 92 dB

### Phase Deviation:

< 0.6 degrees (20 Hz - 20 kHz)

### Power Requirements:

115/230 VAC +/- 15%.

### Weight:

21 pounds (unboxed)

26 pounds (boxed)

### Dimensions:

17"W x 14"D x 4" H (unboxed)

23"W x 18"D x 7" H (boxed)