MULTI MONITOR 220





Bluetooth Qualcomm aptX X



MULTI MONITOR 220 POWERED BLUETOOTH[®] STEREO LOUDSPEAKER SET WITH PHONO INPUT





High-quality phono preamplifier for direct connection of a record player with MM magnet system

Bluetooth[®] input with the high-end audio standard Qualcomm[®] aptX[™] grant music transmission in CD quality



Numerous connection options for flexible and versatile use for smartphone via Bluetooth[®], record player, TV, etc.

Integrated high-performance amplifier module, no additional amplifier is required

Powerful class D amplifier module with 2 x 40 watts $${\rm RMS}\xspace$ power

Connections: - Analogue stereo input (PHONO/LINE) - 3.5 mm analogue stereo input - Optical and coaxial digital input - Subwoofer output

Magnat

Technical modifications and errors excepted • Magnat Audio-Produkte-GmbH • Lise-Meitner-Str.9 • D-50259 Pulheim • www.magnat.de

MULTI MONITOR 220 POWERED BLUETOOTH® STEREO LOUDSPEAKER SET WITH PHONO INPUT

DRIVERS

- 25 mm fmax tweeter with soundguide for optimised dispersion properties and powerful ferrite drive for excellent dynamics
- · FE-dynamics woofer midrange with ceramic-aluminium membrane and low-distortion magnet system
- · Solid metal basket with generous ventilation openings

CABINET

- · Very solid low-resonance construction made of E1 MDF panels
- · Elegant design with matte painted front baffle
- · Detachable front cover with acoustic cloth and invisible magnet fixing
- · Flow-optimised airflex tube with rounded opening
- · Resonance-damping rubber feet for a safe grip

AMPLIFIER & CONNECTIONS

- Analogue stereo input (Cinch R/L) with switchable phono preamplifier for direct connection of a record player with magnet system (MM)
- Additional 3.5 mm analogue stereo input for connecting portable audio devices
- · Optical and coaxial digital input for direct connection of digital audio devices (e.g. TV)
- Sampling rates of all digital inputs up to 24Bit/192kHz
- Subwoofer output for connecting an external active subwoofer
- LED status indicator at the speaker front
- · Control for volume and input selection at the rear panel of the right loudspeaker
- · Complete control is ensured via the supplied remote control (incl. battery)
- Low standby power consumption (<0.5 watts) with auto standby function

CROSSOVER

- · Amplitude- and phase-optimised crossover with high-quality components
- · High-quality terminal with solid gold-plated and capsulated screw connectors

	MULTI MONITOR 220
Principle	Powered stereo bookshelf speaker
	2-way bass reflex, active
Equipment	5" woofer- midrange
	1" dome-tweeter
Power Handling (RMS/Max)	active
Power Output (RMS/Max)	2 x 40 / 2 x 80 W
Impedance	active
Frequency Response	35 – 40,000 Hz
Crossover Frequencies	3,200 Hz
Mains voltage	100 – 240 V
Cabinet surface	Black satin / Black decor
Dimensions (WxHxD)	178 x 298 x 235 mm
Weight	Active speaker: 5.0 kg
	Passive speaker: 4.4 kg
Art.No.	172 600
EAN	40 18843 72600 7

"The Bluetooth[®] " word mark and logos are registered trademarks owned by Bluetooth[®] SIG, Inc. and any use of such marks by Magnat Audio-Produkte GmbH is under license. Other trademarks and trade names are those of their respective owners." Qualcomm is a trademark of Qualcomm Incorporated, registered in the United States and other countries, used with permission. aptX is a trademark of Qualcomm Technologies International, Ltd., registered in the United States and other countries, used with permission.





Technical modifications and errors excepted • Magnat Audio-Produkte-GmbH • Lise-Meitner-Str.9 • D-50259 Pulheim • www.magnat.de