AURORA



AURORA



Floorstander with outstanding sound characteristics and innovative technology



High-quality connecting terminal with solid, gold-plated and capsulated screw connectors with Bi-wiring/Bi-amping optione



New Fluctus tweeter with 28 mm fabric dome and computeroptimised multi-corrugated front panel for perfect dispersion characteristics



Solid crossbeams at the base with height-adjustable massive aluminium cone spikes

AURORA

Ivory White







Ebony Black



AURORA






Drivers

- Tweeter with 28 mm silk compound dome, ferrofluid cooling for high capacity, powerful ferrite double magnet system and new Fluctus acoustic flange geometry
- Woofer-midrange with light long-fibre cone, flat long-fibre dustcap, long-throw surround and highperformance voice coil, optimised for low-distortion signal transmission
- Woofer-midrange with solid and coated steel basket and high-grade, sixfold screwed trim ring

Cabinet

- Solid construction using elaborated struttings (1000, 700)
- Very solid construction (300, Center 30)
- Front and top side in high-quality semi matte painting
- Removable cloth protection cover with hidden magnetic mounts
- Bass reflex construction with airflow-optimised and screwed reflex tubes
- Solid crossbeams at the base with height-adjustable massive aluminium cone spikes



Crossover

- Elaborated phase and amplitude optimized crossover with high-quality components
- High-quality connecting terminal with solid, gold-plated and capsulated screw connectors
- Bi-wiring/Bi-amping option (1000, 700, 300)







HIGHLIGHTS

- Powerful active subwoofer with 30 cm high-power woofer and high-performance amplifier
- Modern design: Silk-matt lacquer combined with modern wood decors
- Sturdy MDF enclosure with one-piece front/top L profile for optimum resonance damping
- Innovative Extended Surface Dampers (ESD)
- · Cloth protection cover with hidden magnetic mounts

Equipment

- Level and crossover-frequency adjustable
- Phase switchable 0° / 180°
- Stereo low level inputs
- · Automatic standby circuit
- Mains switch

Driver

- High-power long-throw woofer with hardened paper cone, high-performance voice-coil and powerful ferrite magnet system
- Woofer frontfire configuration

Cabinet

- Very solid construction
- · Front and top side in high-quality semi matte painting
- Removable cloth protection cover with hidden magnetic mounts
- Bass reflex construction with two airflow-optimised and screwed reflex tubes
- Innovative Extended Surface Dampers (ESD) for a safe grip

Amplifier

- · High performance class AB amplifier
- Real-time Limiter
- Active SPL equalization
- Low standby power consumption (<0.5 watt)

AURORA

AURORA 1000

Principle Equipment

Power Handling (RMS/Max) **Impedance**

Frequency Response Crossover Frequencies

Recommended Amplifier Output

Sensitivity **Cabinet surface Dimensions (WxHxD)**

Weight

Ebony Black Ivory White

3-way bass reflex 2 x 8" woofer 6.5" midrange 1" dome-tweeter

4 - 8 0

93 dB

230/380 W

22 - 42 500 Hz 260 Hz, 3 300 Hz 30 - 380 W

Ebony Black, Ivory White Cabinet: 235 x 1200 x 375 mm

Incl. spikes and Terminal: 305 x 1258 x 393 mm

26.6 kg

Art. No. 134 8030 EAN: 40 29678 48030 9 Art. No. 134 8032 EAN: 40 29678 48032 3



AURORA 700

Principle Equipment

Power Handling (RMS/Max) **Impedance Frequency Response**

Crossover Frequencies Recommended Amplifier Output

Sensitivity **Cabinet surface**

Dimensions (WxHxD)

Weight

Ebony Black Ivory White

3-way bass reflex 2 x 6.5" woofer

6.5" midrange 1" dome-tweeter

4 - 8 Ω

25 - 42 500 Hz 290 Hz. 3 300 Hz 30 - 300 W 92 dB

Ebony Black, Ivory White Cabinet: 195 x 1100 x 325 mm

Incl. spikes and Terminal: 265 x 1158 x 343 mm

Art. No. 134 8020 EAN: 40 29678 48020 0

Art. No. 134 8022 EAN: 40 29678 48022 4

19.9 kg



AURORA

AURORA 300

Principle 2-way bass reflex Equipment 6.5" midrange 1" dome-tweeter

Sensitivity90 dBCabinet surfaceEbony Black, Ivory WhiteDimensions (WxHxD)Cabinet: 195 x 357 x 315 mm

Incl. spikes and Terminal: 195 x 357 x 333 mm

7.5 kg

Ebony Black Art. No. 134 8010 EAN: 40 29678 48010 1 Ivory White Art. No. 134 8012 EAN: 40 29678 48012 5



AURORA Center 30

Weight

Principle 2-way bass reflex
Equipment 2 x 5" woofer-midrange
1" dome-tweeter
Power Handling (RMS/Max) 90/150 W

Impedance $4 - 8 \Omega$ Frequency Response34 - 42 500 HzCrossover Frequencies3 300 HzRecommended Amplifier Output20 - 150 WSensitivity90 dB

Cabinet surfaceEbony Black, Ivory WhiteDimensions (WxHxD)Cabinet: 490 x 177 x 285 mm

Incl. spikes and Terminal: 490 x 177 x 303 mm

Weight 9.4 kg

Ebony Black Art. No. 134 8040 EAN: 40 29678 48040 8 Ivory White Art. No. 134 8042 EAN: 40 29678 48042 2

AURORA

AURORA Sub 30A

Principle
Equipment
Power Output (RMS/Max)
Frequency Response
Crossover Frequencies
Cabinet surface
Dimensions (WxHxD)

Weight

Ebony Black Ivory White Powered bass reflex subwoofer

12" powered subwoofer

125 / 250 W

20 - 150 Hz

50 - 150 Hz adjustable

Ebony Black, Ivory White

Cabinet: 350 x 465 x 415 mm

Incl. spikes and Terminal: 350 x 465 x 445 mm

Art. No. 134 8050 EAN: 40 29678 48050 7 Art. No. 134 8052 EAN: 40 29678 48052 1

19.5 kg

