



EPIKORE 11

40 YEARS OF LOUDSPEAKER EXCELLENCE

The DALI EPIKORE 11 is the continuation of a rich bloodline of high-end DALI loudspeakers. From the DALI 40 SE and MegaLine, to the EUPHONIA, EPICON and our current high-end flagship, the DALI KORE, the EPIKORE 11 celebrates four decades of excellence within loudspeaker design and manufacturing.

EVOLUTION THROUGH KORE TECHNOLOGY

Bridging the gap between the DALI EPICON series and DALI KORE, the EPIKORE 11 incorporates many of the groundbreaking technologies from our flagship KORE speaker and sets new standards for high-end, low-distortion loudspeaker design.

Scan QR-code for more information.



DALI EPIKORE 11 Specifications

Frequency range	29 - 34.000 Hz ±3 dB	
Sensitivity	89 dB @ 1 m for 2.83 V	
Nominal impedance	4 ohm	
Maximum SPL	116 dB	
Crossover frequency	170 / 370 / 3,100 / 12,500 Hz	
Crossover principle	4½-way	
Recommended amplifier power	40 - 1000 Watt	
High frequency driver(s)	10 × 55 mm ribbon 1 x 35 mm soft dome	
High frequency diaphragm	Planar electrostatic ribbon Soft woven fabric	
Low/Mid frequency driver(s)	4 x 8 inch 1 x 6½ inch	
Low/Mid frequency diaphragm	Wood fibre cone	
Connection input(s)	Bi-wire	
Enclosure type	Bass reflex	
Bass reflex tuning frequency	24 Hz	
Recommended placement	Floor	
Recommended distance from rear wall	35 - 120 cm	
Dimensions (H x W x D)	1602 x 422 x 554 mm 63 x 16.6 x 21.8 inches	
Weight incl. grille	75.6 kg 166.6 lb	
Shipping weight	176 kg (pair) 388 lb (pair)	
Finishes	High Gloss Black High Gloss Walnut High Gloss Maroon	
Accessories	Manual Inlay card Cleaning cloth Spike outriggers (two pairs) Magnetic spike feet	Terminal jumpers Floor protection pads 5 mm Allen key Magnetic front grille
Spike thread size	M12-1	

The information provided in this manual is subject to change without notice.